



Rec'd PCT/PTO 2538 31 DEC 2004 #2



INVESTOR IN PEOPLE

PRIORITY DOCUMENT
SUBMITTED OR TRANSMITTED IN
COMPLIANCE WITH
RULE 17.1(a) OR (b)

The Patent Office
Concept House
Cardiff Road

Newport REC'D 25 AUG 2003
South Wales
NP10 8QQ WIPO PCT

I, the undersigned, being an officer duly authorised in accordance with Section 74(1) and (4) of the Deregulation & Contracting Out Act 1994, to sign and issue certificates on behalf of the Comptroller-General, hereby certify that annexed hereto is a true copy of the documents as originally filed in connection with the patent application identified therein.

In accordance with the Patents (Companies Re-registration) Rules 1982, if a company named in this certificate and any accompanying documents has re-registered under the Companies Act 1980 with the same name as that with which it was registered immediately before re-registration save for the substitution as, or inclusion as, the last part of the name of the words "public limited company" or their equivalents in Welsh, references to the name of the company in this certificate and any accompanying documents shall be treated as references to the name with which it is so re-registered.

In accordance with the rules, the words "public limited company" may be replaced by p.l.c., plc, P.L.C. or PLC.

Re-registration under the Companies Act does not constitute a new legal entity but merely subjects the company to certain additional company law rules.


Signed

Dated 28 July 2003

An Executive Agency of the Department of Trade and Industry

BEST AVAILABLE COPY

Patents Act 1977
Rule 1



23 JUN 02 E72763-1 001559
P01/7700 026-02 1375.3

Request for grant of a patent

(See the notes on the back of this form. You can also get an explanatory leaflet from the Patent Office to help you fill in this form)

The Patent Office

Cardiff Road
Newport
South Wales
NP10 8QQ

1. Your reference
MJ/CS/OML.62
2. Patent application number
(The Patent Office will fill in this part)
21 JUN 2002 0214373.3
3. Full name, address and postcode of the or of each applicant (*underline all surnames*)
Owen Mumford Limited
Brook Hill
Woodstock
Oxon OX20 1TU
Patents ADP number (*if you know it*) 04413738001
If the applicant is a corporate body, give the country/state of its incorporation United Kingdom
4. Title of the invention
Improvements relating to finger pricking lancets
5. Name of your agent (*if you have one*)
Wynne-Jones Laine & James
"Address for service" in the United Kingdom to which all correspondence should be sent (*including the postcode*)
22 Rodney Road
Cheltenham
Gloucestershire GL50 1JJ
Patents ADP number (*if you know it*) 1792001 ✓
6. If you are declaring priority from one or more earlier patent applications, give the country and the date of filing of the or of each of these earlier applications and (*if you know it*) the or each application number

Country	Priority application number (<i>if you know it</i>)	Date of filing (<i>day / month / year</i>)
---------	--	---
7. If this application is divided or otherwise derived from an earlier UK application, give the number and the filing date of the earlier application

Number of earlier application	Date of filing (<i>day / month / year</i>)
-------------------------------	---
8. Is a statement of inventorship and of right to grant of a patent required in support of this request? (*Answer 'Yes' if:*
a) any applicant named in part 3 is not an inventor, or
b) there is an inventor who is not named as an applicant, or
c) any named applicant is a corporate body.
See note (d))
Yes

BEST AVAILABLE COPY

Patents Form 1/77

9. Enter the number of sheets for any of the following items you are filing with this form.
Do not count copies of the same document

Continuation sheets of this form

Description

4

Claim(s)

Abstract

Drawing(s)

141

10. If you are also filing any of the following, state how many against each item.

Priority documents

Translations of priority documents

Statement of inventorship and right to grant of a patent (*Patents Form 7/77*)

Request for preliminary examination and search (*Patents Form 9/77*)

Request for substantive examination (*Patents Form 10/77*)

Any other documents
(please specify)

11.

I/We request the grant of a patent on the basis of this application.

Signature

Wynne-Jones Laine & James

Date 20.06.2002

12. Name and daytime telephone number of person to contact in the United Kingdom

Mr M James 01242 515807

Warning

After an application for a patent has been filed, the Comptroller of the Patent Office will consider whether publication or communication of the invention should be prohibited or restricted under Section 22 of the Patents Act 1977. You will be informed if it is necessary to prohibit or restrict your invention in this way. Furthermore, if you live in the United Kingdom, Section 23 of the Patents Act 1977 stops you from applying for a patent abroad without first getting written permission from the Patent Office unless an application has been filed at least 6 weeks beforehand in the United Kingdom for a patent for the same invention and either no direction prohibiting publication or communication has been given, or any such direction has been revoked.

Notes

- If you need help to fill in this form or you have any questions, please contact the Patent Office on 08459 500505.
- Write your answers in capital letters using black ink or you may type them.
- If there is not enough space for all the relevant details on any part of this form, please continue on a separate sheet of paper and write "see continuation sheet" in the relevant part(s). Any continuation sheet should be attached to this form.
- If you have answered 'Yes' Patents Form 7/77 will need to be filed.
- Once you have filled in the form you must remember to sign and date it.
- For details of the fee and ways to pay please contact the Patent Office.

BEST AVAILABLE COPY

Patents Form 1/77

"Improvements relating to Finger Pricking Lancets"

5 . A conventional lancet comprises a needle held by a support body that has been moulded about the needle. In one form of lancet, a removable guard is moulded at the same time to cover the point of the needle. The guard can be snapped away to expose the needle for use. Conventional moulding techniques tend to subject the needle tip to a bending force so that it can be deflected to one side and thus becomes offset from the body. This can be a major disadvantage when the lancet is used in conjunction with an automatic finger pricking device, where the lancet is held by its body and the needlepoint is driven through a small hole in a support platform held against the blood-sampling site. Any misalignment of the needle could cause increased discomfort during the pricking operation. Also, recent diagnostic techniques may include a blood collecting test strip at the sampling site, so it is important to prevent any misalignment of the needle tip to avoid contact between the needle tip and the support platform, or between the needle tip and the wrong part of the test strip.

10 It is the object of this invention to alleviate the problem of the bending of the needle tip.

15 Accordingly this invention provides a lancet with a removable guard located over the point of a needle part of the lancet, the guard being formed from a moulded plastics material with an outer edge thickened region leading from the end of the guard remote from the needle point to a thinner section of the plastics material approaching the needle point.

20 When forming the lancet in this way, during the moulding process, the plastics material is caused to be slowed temporarily as it meets the interface between the outer edge thickened region and the thinner section approaching the needle tip. Ideally the guard will be formed with a centrally positioned hole

close to the end of the guard remote from the needle point. This hole will be created by a pin forming part of the mould for creating the guard. During the moulding process the plastics material will be caused to flow around the central pin. This helps to create a more even flow to both sides of the guard.

5 Consequently, during manufacture, the needle tip will be subjected to controlled balanced forces which act behind the needle point, subjecting it to a lower bending force than with conventional procedures.

Ideally the plastics material forms a further thickened region about the needle tip, but separated from the outer edge region by said thinner section.

10 This is to protect the needle tip from being accidentally being displaced through the side of the plastics material prior to use. Although the needle tip itself will be surrounded by a thickened region of material, the slowing down of the material in the thinner section will be sufficient to limit the potential for a bending force to be applied to the needle tip.

15 Ideally the guard will be of generally tab-like form, with the thickened region forming arc-like portions on the two side edges of the guard. The guard can be interconnected with a support body holding the needle via a breakable neck portion moulded with the guard and the support body.

20 The invention also extends to a method of forming a lancet in which a needle is held in a mould formed to create a support body for holding the base portion of the needle and a removable guard about the pointed needle tip, the mould having an entry point for plastics material, at the end of the guard remote from the needle point, leading to an outer edge thickened hollow region which in turn leads to a thinner hollow section approaching the needle tip and plastics
25 material is injected into the mould via the entry point to create the guard about the needle tip.

In the preferred performance of the method the plastics material flows

around both sides of a pin located close to said entry point towards said edge thickened hollow and ideally may flow into an enlarged hollow region surrounding the needle tip from said thinner hollow section. It is preferred that the plastics material flows from the guard through a neck portion of the mould leading to the part of the mould defining the support body.

The invention may be performed in various ways and a preferred embodiment thereof will now be described in reference to the accompanying drawings, in which:-

Figures 1 and 2 are plan, side views respectively of a lancet of this invention; and




Figure 3 is a vertical section through the lancet of Figures 1 and 2.

The lancet shown in the drawings incorporates a needle 1 (Figure 3) held within a support body 2. The tip portion 3 of the needle (having an angled point 4) is protected by a guard 5. The support body 2 and the guard 5 are moulded simultaneously about the needle 1. During moulding the needle is held by pins which create passageways 6 and 7 within the support body 1. The plastics material is injected through an entry point of the mould at the location 8 and is caused to deflect around a pin which creates the hole 9 in the guard 5, so as to increase the balance of flow of material to either side of the pin 9. Conventionally several lancets are moulded at one time to either side of a spine. The plastics material therefore enters at the location 8 at an angle and tends to bend around the far corner of the part of the mould defining the lancet such that there will be an uneven flow of pressure on to the two sides of the end portion 3 of the needle which can tend to bend it, particularly when the plastics material hits the angled face 4. There is then the possibility that the tip 3 will be bent out of shape within the guard 5 which can make the lancet more difficult to use with a finger pricker device when the guard has been removed.

In order to minimise the tendency for the plastics material to bend the tip 3 of the needle out of shape, the mould is formed such that the mould material is initially encouraged to divide and flow through outer thickened regions 10. These surround a thinner portion 11 with the thickened portion 10 terminating before it reaches the region of the needle tip 3. At this point 12 the plastics material is therefore caused to slow down resulting in greater equalisation of the flow speed of the plastics material to either side of the needle tip 3. Immediately around the needle tip 3 however the mould is formed to create a thickened region 13 to provide adequate protection for the needle tip. Although the flow of plastics material is slowed by the narrow portion 12, there is still sufficient force (although now much more evenly distributed about the needle tip 3) to push the needle back against a rear stop (which creates the hole 14) in the support body 2 to ensure that the projecting part of the needle 1 is of a required length.

In use the guard 5 is twisted to shear the material about a neck 15 so that the guard can be removed to expose the needle tip 3 for use. The moulding method employed which, in particular, creates the narrowed portion 12 between the thickened outer edge regions 10 and the thickened region 13 surrounding the needle tip 3, helps to ensure that the exposed needle tip is unlikely to be in a bent condition when the guard 5 is detached.

1/1



BEST AVAILABLE COPY